

## SC Duplex / LC Quad Patch Panel 24 Port

Our new improved range of sliding drawer panels now have interchangeable front plates for maximum versatility.

The sliding style tray allows easy access to the fibre termination compartment without having to remove the panel from the rack; ensuring panels can be reconfigured easily.

The tray can also be fixed at an angle whilst working so engineers' hands remain free. The tray is secured with two quick release fastenings. Standard 19" width with movable mounting brackets enable the panel to be mounted flush or recessed. Removable front plate allows for easy installation of adapters. One base accepts 3 different front panels to allow for maximum flexibility in supply. The panels can be supplied fully loaded with adapters, partially loaded or unloaded.

SC Duplex / LC Quad panels are suitable for up to 24 adapters in one line.

Features & Benefits
<ul style="list-style-type: none"> <li>• Designed for installation with 19" racks to IEC 297-3</li> <li>• Accommodates up to 48 splices via 2x 24f splice cassettes (double stacked)</li> <li>• 2 x 26mm and 2 x 22mm cable entry holes to rear of panel</li> <li>• Mounting brackets can be positioned flush, recessed or protruding</li> <li>• Screen printed port identification to the front of panel</li> <li>• Maximum 96 connections using LC Quad adapters</li> <li>• Maximum 48 connections using SC Duplex adapters</li> <li>• Removable faceplate allows easy loading of adapters and reduced stock holding</li> <li>• Range of cable management options are available</li> </ul>

Available Kits
<ul style="list-style-type: none"> <li>• Kit 1 - 4 bunny clips, 1x 20mm cable gland, 6x 100mm cable ties + 4 cage nuts</li> <li>• Kit 2 - Kit 1 + Splice Bridge</li> <li>• Kit 3 - Kit 1 + Splice Cassette</li> </ul>

Application
<ul style="list-style-type: none"> <li>• Optical Splicing &amp; Patching</li> <li>• Data centres, premise installations, telecommunication networks</li> <li>• Ethernet, Fibre Channel, ATM, LAN, MAN, and WAN</li> <li>• Data Communication</li> <li>• Suitable for all Lite Linke pre-terminated solutions</li> </ul>

Description	Stock Code
24 Port Sliding Patch Panel for SC Duplex Multimode Adaptors	PPLLSM-SCD/xx
24 Port Sliding Patch Panel for SC Duplex Singlemode Adaptors	PPLSS-SCD/xx
24 Port Sliding Patch Panel for LC Quad Multimode Adaptors	PPLLSM-LCQ/xx
24 Port Sliding Patch Panel for LC Quad Singlemode Adaptors	PPLSS-LCQ/xx

where xx is number of adaptors



Specifications	
Element	Characteristic
U Size	1U
Width	433mm
Depth	243mm
Cable Entry Slots	2 x 26mm / 2 x 22mm
Cable Anchor Points	Rear and External
Material	Cold-rolled Steel
Colour	Black (Powder Coated) RAL: 9005
Compliance	RoHS, REACH

